

# LED Street Lantern



## TSL-S295



### Features

- Modular design by Die-casting aluminum
- Power from 50W to 300W
- Offer durable lifespan up to 50,000 hours
- Compliance Standard
- LM79, IEC/EN 60598-2-1
- TUV, ETL, DLC Approved
- IP66 protection rating
- 5 years warranty

### Advantages

- Individual LED module, enables good heat dissipation
- Bat optical lens, ensure max light uniformity
- compatible for dimmable, photosensor and smart LCU
- Toolless for unit replacement



### Technical specification

Model	Power	LED Source	Lumen	CRI	CCT	Dimensions(mm)
TSL-S295-W50	50W	Lumileds 3030	7200lm	>80	3000/4000/5500K	340×290×87mm
TSL-S295-W100	100W		12000lm			421×290×87mm
TSL-S295-W150	150W	Lumileds 3030	18000lm	>80	3000/4000/5500K	501×290×87mm
TSL-S295-W200	200W		24000lm			582×290×87mm
TSL-S295-W240	240W	Lumileds 3030	28800lm	>80	3000/4000/5500K	662×290×87mm
TSL-S295-W300	300W		36000lm			743×290×87mm

Remark: the power 30W of single module is available upon request.

### Photometric Curve

